

Auto Gold[®] ATF DM



Automatic Transmission Fluid

General Description

Auto Gold[®] ATF DM meets the special frictional characteristics, transmission cleanliness and low temperature pumpability required for pre-2006 GM and Ford vehicles.

Careful base oil selection assures excellent low temperature performance for ATF fluids required by GM and Ford. The specialized performance additive provides superior oxidation resistance for extended use under high temperature operating conditions and smooth power transfer during shift cycles. Auto Gold ATF DM contains special additives to prevent oil seal deterioration and provides superior resistance to foaming. The superb frictional properties needed in GM and Ford ATF fluids, which affect the shift feel, are retained for an extended period of time.

There is an increasing trend toward manufacturers using ATF (Automatic Transmission Fluid) for hydraulic applications, especially in cold weather environments. The superior anti-wear performance built into Auto Gold ATF DM assures proper protection of these hydraulic pumps and systems where Dexron, Dexron II, Dexron III, and Mercon fluids are recommended by the manufacturer.

Features and Benefits

- **Frictional Properties:** Outstanding frictional characteristics provide smooth shifting and excellent retention of shifting performance throughout the service interval.
- **High Temperature Protection:** Excellent oxidation and sludge protection for high transmission temperatures experienced by modern cars.
- **Cold Flow:** Superior cold temperature flow characteristics assures ease of pumping and good shifting capabilities, even at extremely low temperatures.
- **Manufacturer Requirements:** Auto Gold[®] ATF DM continues to meet Allison C-4 specification. It also meets pre 2006 GM and Ford vehicle requirements. It should not be used in applications calling for Dexron VI, Mercon V, SP, and Type F, Chrysler ATF +3, +4, CVT, and 6-speed transmissions.

PDS-057-06

Auto Gold[®] ATF DM

AUTOMATIC TRANSMISSION FLUID

Typical Application

Suitable for use in all applications where manufacturers recommend:

- Dexron[®] III-H,G
- Dexron[®] IIE
- Dexron[®] II
- Dexron[®]
- Type A, Suffix A
- Mercon[®]
- Ford M2C-138CJ
- Ford M2C-166H
- Ford Type H
- Allison C-4

Typical Customer

Owners and operators of:

- Most GM and Ford automobiles and light trucks
- Allison C-4 applications
- Selected hydraulic systems

Typical Properties

Qualifications	Auto Gold ATF DM
Viscosity, cSt @40°C	34.4
@100°C	7.0
Brookfield @ -40 cP	18,000
Viscosity Index	171
API Gravity / lbs./gal	32.9 / 7.17
Pour Point, °F / °C	> -54 / -48
Flash Point, °F	417
Color	RED

The typical properties listed reflect the general characteristics of the product, and are not manufacturing specifications. Normal batch-to-batch variations should be expected.

Health & Safety

A complete safety data sheet is available by calling 1-651-355-8438 or visit www.cenex.com.