

General Description

Qwiklift HTB is a multi-functional universal tractor hydraulic fluid formulated specifically for agriculture and construction equipment. It is designed to lubricate transmissions, differentials, final drives, wet brakes, hydraulic systems, hydrostatics, PTO's and power steering components that call for a single fluid.

Qwiklift HTB is specially formulated with high viscosity index Group II base oils and a field proven state-of-the-art additive system that provides unparalleled wear protection for heavily loaded gears, clutches and hydraulic pumps. The formulation has outstanding shear stability, exceptional resistance to high temperature oxidation and thermal stress to extend component life.

This oil also has the optimum balance of frictional properties that minimize the noise and damage caused by wet brake chatter, while maximizing brake and clutch capacity providing smooth operation. Additionally, designed to provide superior transmission and hydraulic performance over a wide temperature range while protecting against corrosion of yellow metals, rust, and foaming.

Qwiklift HTB Low Vis is recommended when extremely cold temperature start-up and operation is essential or for use in certain types of hydrostatic drives calling for a low viscosity fluid.

Features and Benefits

- **Wear Protection:** Contains anti-wear additives and proven to protect gears, pumps and other moving parts from wear resulting in extended equipment life.
 - **Enhanced Friction Control:** Outstanding frictional properties provide smooth clutch engagements under heavy loads while improved brake chatter control results in smooth stopping and less noise during operation—ultimately improving productivity.
 - **Oxidation Control:** Superior oxidation and thermal stability reduces oil degradation and keeps the system free from sludge, varnish, and acids, which in turn contributes to longer equipment and component life.
 - **Oil Durability:** Operates effectively over a long period of time in a wide variety of equipment, duty cycles, temperatures, and field conditions. It prolongs the life of clutch materials, elastomers and seals, while reducing leakage and maintenance costs.
 - **Compatibility:** Exceptional filterability and compatibility with OEM proprietary fluids and competitive THF fluids.
 - **Expect superior performance in:** Agriculture, off-highway and construction equipment calling for a J20-C, THF or UTTO fluid.
- Qwiklift HTB has API GL-4 gear performance. Do not use in differentials and axles that call for API GL-5 gear performance.**

Check the Farm Tractor Lubrication Guide for recommendations and the Cenex THF cross-over guide for OEM and competitive products.

Qwiklift® HTB®

Universal Tractor Hydraulic, Transmission and Wet Brake Fluid

Qwiklift HTB Formal Approvals:

Volvo for WB-101 **Massy Ferguson/GIMA** for CMS M-1145 **Ford** M2C-134D, AGCO 821XL
Z-F transmissions/axles specifications:
TE-ML 03E, 05F, 06K, 17E, 21F
Factory fill approved: AGCO (Cat Challengers, AGCO Challengers, Massy Ferguson, New RoGators, TerraGators, and Air Coups. CVT, see Fendt on the right.

CHS Lubricants recommends that Qwiklift HTB Low Vis is suitable for use in the following applications:
John Deere: J20D/B, J21A
Versatile: Hy-Gear Fluid, Specification 24M

CHS Lubricants recommends that Qwiklift HTB is suitable for use in the following applications:

AGCO: Power Fluid 821XL, 821 **Case-IH:** Hy-Tran® Ultra, Hy-Tran® Plus, Hy-Tran®, MAT-3540, MAT-3505, MS-1210, MS-1209, MS-1207, MS-1206, JIC 144/145, Powergard PTF
Caterpillar: MTO **Deutz/Allis:** Power Fluid 821
Fendt CVT: 1000 hour drain (shortened interval)
Ford New Holland: Mastertran Ultraction (MAT 3540), M2C-134 D/C/B/A, MAT- 3525, M2C-41B, M2C- 53A/B, M2C-86B **Hesston/Fiat:** Olio fiat Tutela Multi-F **John Deere:** Hy-Gard; J20C/A, JD 303, J14C/B **Kubota:** Kubota UDT Fluid, Transdraulic Fluid **Massey Ferguson:** M-1145, 1143 Permatran III, MF-1127A/B, MF-1129A, **Steiger:**Hydraulic/Transmission Fluid 17001
Landini: Tractor II Hyd Fluid **Versatile:** HyGear Fluid, Specification 23 **White/Oliver/MM:** AG ONE, Universal Fluid, Type 55, Q-1826 HTF **Zetor:** OT-H, GL-4

Typical Properties

Physical Tests	Qwiklift HTB	Qwiklift HTB Low Vis
SAE Grade (approx.)	10W-30	5W-20
API Gravity / lbs. gal	29.5 / 7.32	31.1 / 7.25
Flash Point, °C (°F)	220 (428)	176 (350)
Pour Point, °C (°F)	-45 (-49)	-51 (-60)
Viscosity, cSt @ 100°C	9.5	7.2
Viscosity, cSt @ 40°C	61	34
Viscosity Index	140	183
Brookfield Viscosity cP @ -20°C	4,500	1,300
Brookfield Viscosity cP @ -35°C	55,000	
Brookfield Viscosity cP @ -40°C		18,000
Foam D-892	Pass	Pass
DKA Oxidation Test	Pass	Pass
Seal Compatibility	Pass	Pass
OEM Shear Stability	Pass	Pass
API Gear Performance	GL-4	GL-4
Color	Green	Blue

The typical properties listed reflect the general characteristics of the product, and are not manufacturing specifications. Normal batch-to-batch variations should be expected.

Health & Safety

A complete safety data sheet is available by calling 1-651-355-8438 or visit www.cenex.com.

PDS-QWI-THF5-14