

# SAFETY DATA SHEET

## Section 1. Identification

Manufacturer Transportation Emergency (CHEMTREC) : 1-800-424-9300

CHS Inc.

CCN23163

P.O. Box 64089
Mail station 573
Technical Information : 1-651-355-8443

St. Paul, MN 55164-0089 SDS Information : 1-651-355-8445

 Product name
 : Auto Gold HMO 10W30, 10W40
 SDS no.
 : 0196-090771

 Common name
 : Motor Oil SAE 10W-30, 10W-40
 Revision date
 : 03/01/2023

Chemical name : Lubricating oil. Chemical formula : Mixture

Chemical family : Hydrocarbon.

Relevant identified uses of the substance or mixture and uses advised against

Lubricant.

#### Section 2. Hazards identification

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or

mixture

: RESPIRATORY SENSITIZATION - Category 1

SKIN SENSITIZATION - Category 1

**GHS label elements** 

Hazard pictograms



Signal word : Danger

**Hazard statements**: H317 - May cause an allergic skin reaction.

H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Precautionary statements

General : Read label before use. Keep out of reach of children. If medical advice is needed, have product container or

label at hand.

**Prevention**: Wear protective gloves. Wear respiratory protection. Avoid breathing vapor.

Response : IF INHALED: Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory

symptoms: Call a POISON CENTER or doctor. Wash contaminated clothing before reuse. IF ON SKIN: Wash

with plenty of water.

Storage : Not applicable.

Disposal : Dispose of contents and container in accordance with all local, regional, national and international regulations.

Hazards not otherwise classified : None known.

Hazardous Material Information System (U.S.A.)

Health: 2 \* Flammability: 1 Physical hazards: 0

National Fire Protection Association (U.S.A.)

Health: 2 Flammability: 1 Instability: 0

# Section 3. Composition/information on ingredients

Substance/mixture : Mixture

Chemical name : Lubricating oil.

Other means of identification : Motor Oil SAE 10W-30, 10W-40

Ingredient name	%	CAS number
Distillates (petroleum), hydrotreated heavy paraffinic	≥80 - ≤100	64742-54-7
	≥0.3 - <1	28777-98-2

The exact percentage (concentration) in the composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

There are no ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

#### Section 4. First aid measures

#### **Description of necessary first aid measures**

Eye contact : If material comes in contact with the eyes, immediately wash the eyes with large amounts of water for 15

minutes, occasionally lifting the lower and upper lids. Get medical attention.

Inhalation : If person breathes in large amounts of material, move the exposed person to fresh air at once. If breathing has

stopped, perform artificial respiration. Keep the person warm and at rest. Get medical attention as soon as

possible.

Skin contact : If the material comes in contact with the skin, wash the contaminated skin with soap and water promptly. If the

material penetrates through clothing, remove the clothing and wash the skin with soap and water promptly. If

irritation persists after washing, get medical attention immediately.

: If material has been swallowed, do not induce vomiting. Get medical attention immediately.

# Most important symptoms/effects, acute and delayed

#### Potential acute health effects

Ingestion

**Eye contact**: No known significant effects or critical hazards.

Inhalation : May cause allergy or asthma symptoms or breathing difficulties if inhaled.

**Skin contact**: May cause an allergic skin reaction.

**Ingestion**: No known significant effects or critical hazards.

#### Over-exposure signs/symptoms

Eye contact : Adverse symptoms may include the following: pain or irritation, watering, redness.

Inhalation : Adverse symptoms may include the following: respiratory tract irritation, coughing.

Skin contact : Adverse symptoms may include the following: irritation, redness.

**Ingestion**: No known significant effects or critical hazards.

#### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested

or inhaled.

Specific treatments : No specific treatment.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be

dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing

thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

#### Section 5. Fire-fighting measures

#### Extinguishing media

Suitable extinguishing media : Use water spray to cool fire exposed surfaces and to protect personnel. Foam, dry chemical or

water spray (fog) to extinguish fire.

Unsuitable extinguishing media

: None known.

Specific hazards arising from the chemical

: Toxic fumes gases or vapors may evolve on burning.

Hazardous thermal decomposition products

: No specific data.

Special protective actions for fire-fighters

: When fighting fires wear full turnout gear and self contained breathing apparatus. Water may cause splattering. Material floats on water.

Special protective equipment for fire-fighters

: Not applicable.

#### Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: Keep unnecessary and unprotected personnel from entering. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

# Methods and materials for containment and cleaning up

Spill

: Contain with dikes or absorbent to prevent migration to sewers/streams. Take up small spill with dry chemical absorbent; large spills may require pump or vacuum prior to absorbent. May require excavation of severely contaminated soil.

# Section 7. Handling and storage

#### Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see Section 8). Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate.

Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking.

Conditions for safe storage, including any incompatibilities

: Do not store above the following temperature: 113°C (235.4°F). Odorous and toxic fumes may form from the decomposition of this product if stored at excessive temperatures for extended periods of time. Store in accordance with local regulations. Store in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10). Use appropriate containment to avoid environmental contamination.

# Section 8. Exposure controls/personal protection

#### **Control parameters**

#### **United States**

#### Occupational exposure limits

Ingredient name	Exposure limits	
Distillates (petroleum), hydrotreated heavy paraffinic	OSHA PEL (United States, 5/2018).  TWA: 5 mg/m³ 8 hours.  ACGIH TLV (United States, 3/2018).  TWA: 5 mg/m³ 8 hours. Form: Inhalable fraction  NIOSH REL (United States, 10/2016).  TWA: 5 mg/m³ 10 hours. Form: Mist  STEL: 10 mg/m³ 15 minutes. Form: Mist	

Appropriate engineering controls

: Use only with adequate ventilation.

**Environmental exposure controls** 

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.

#### **Individual protection measures**

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Recommended: Splash goggles and a face shield, where splash hazard exists.

Skin protection Hand protection Body protection

: 4 - 8 hours (breakthrough time): Nitrile gloves.: Recommended: Long sleeved coveralls.

Other skin protection

: Recommended: Impervious boots.

Respiratory protection

: If ventilation is inadequate, use a NIOSH-certified respirator with an organic vapor cartridge and P95 particulate filter.

# Section 9. Physical and chemical properties

<u>Appearance</u>		Relative density	: 0.87 to 0.88
Physical state	: Liquid.	Evaporation rate	: <1 (Butyl acetate = 1)
Color	: Amber.	Solubility	: Insoluble in the following materials: cold water and hot water.
Odor	: Mild.	Solubility in water	: Insoluble
Odor threshold	: Not available.	Partition coefficient: n-	: Not available.
рН	: Not available.	octanol/water	
Melting point	: Not available.	Auto-ignition temperature	: >260°C (>500°F)
Boiling point	: Not available.	Decomposition temperature	: Not available.
Flash point	: Closed cup: >221°C (>429.8°F)	SADT	: Not available.
Flammability	: Not available.	Viscosity	: Not available.
Lower and upper	: Not available.	Vapor pressure	: <0.13 kPa (<1 mm Hg) (68°F)
explosive (flammable) limits		Vapor density	: Not available.

# Section 10. Stability and reactivity

Reactivity : No specific test data related to reactivity available for this product or its ingredients.

Chemical stability : The product is stable.

Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : No specific data.

Incompatible materials : Not available.

Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

# Section 11. Toxicological information

#### Information on toxicological effects

#### **Acute toxicity**

There is no data available.

## Irritation/Corrosion

Skin: Not hazardous (per manufacturer).Eyes: Not hazardous (per manufacturer).Respiratory: Not hazardous (per manufacturer).

#### Sensitization

Product/ingredient name	Route of exposure	Species	Result
Dihydro-3-(octadecenyl)furan- 2,5-dione	skin	Guinea pig	Sensitizing

#### **Mutagenicity**

There is no data available.

# Carcinogenicity

There is no data available.

### Reproductive toxicity

There is no data available.

#### **Teratogenicity**

There is no data available.

### Specific target organ toxicity (single exposure)

There is no data available.

# Specific target organ toxicity (repeated exposure)

There is no data available.

# **Aspiration hazard**

Name	Result	
Distillates (petroleum), hydrotreated heavy paraffinic	ASPIRATION HAZARD - Category 1	

# Information on the likely routes of

exposure

: Dermal contact. Eye contact. Inhalation. Ingestion.

# Section 12. Ecological information

# **Toxicity**

There is no data available.

### Persistence and degradability

There is no data available.

# **Bioaccumulative potential**

There is no data available.

#### **Mobility in soil**

Soil/water partition coefficient (Koc) : There is no data available.

Other adverse effects

: No known significant effects or critical hazards.

# Section 13. Disposal considerations

Disposal methods

: Disposal of this product, solutions and any by-products should comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

# Section 14. Transport information

DOT IDENTIFICATION NUMBER Not applicable.

DOT proper shipping name Not applicable.

DOT Hazard Class(es) Not applicable. Not applicable.

**DOT-TDG EMER. RESPONSE** 

Not applicable

**GUIDE NO.** 

# Section 15. Regulatory information

U.S. Federal regulations

: TSCA 4(a) proposed test rules: Dihydro-3-(octadecenyl)furan-2,5-dione TSCA 4(a) final test rules: 2-Butenedioic acid (E)-, di-C8-18-alkyl esters

TSCA 8(a) PAIR: 2-Butenedioic acid (E)-, di-C8-18-alkyl esters; Diphenylamine; 3-(Decyloxy)

tetrahydrothiophene 1,1-dioxide

TSCA 8(a) CDR Exempt/Partial exemption: Not determined

United States inventory (TSCA 8b): All components are active or exempted.

Clean Water Act (CWA) 307: Zinc bis(O,O-diisooctyl) bis(dithiophosphate); Zinc O,O,O',O'-tetrakis

(1,3-dimethylbutyl) bis(phosphorodithioate), Benzene

Clean Water Act (CWA) 311: Ethylenediamine; Fumaric acid; Vinyl acetate; Benzene

Clean Air Act Section 602 Class I Substances Clean Air Act Section 602 Class II Substances : Not listed : Not listed

**DEA List I Chemicals (Precursor Chemicals)** 

: Not listed

**DEA List II Chemicals (Essential Chemicals)** 

: Not listed

Clean Air Act Section 112(b) Hazardous Air Pollutants (HAPs)

: Listed

# SARA 302/304

#### Composition/information on ingredients

			SARA 302 TPQ		SARA 304 RQ	
Name	%	EHS	(lbs)	(gallons)	(lbs)	(gallons)
Ethylenediamine	<0.1	Yes.	10000	1337.1	5000	668.5
Sulphur Dioxide	≤0.0025	Yes.	500	-	500	-
Vinyl acetate	≤0.001	Yes.	1000	129	5000	644.8

SARA 304 RQ : 27777777.8 lbs / 12611111.1 kg [3807432.1 gal / 14412698.4 L]

**SARA 311/312** 

Hazard classifications

: RESPIRATORY SENSITIZATION - Category 1

SKIN SENSITIZATION - Category 1

#### Composition/information on ingredients

Name	Classification
Distillates (petroleum), hydrotreated heavy paraffinic Dihydro-3-(octadecenyl)furan-2,5-dione	ASPIRATION HAZARD - Category 1 SKIN CORROSION/IRRITATION - Category 2 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A RESPIRATORY SENSITIZATION - Category 1 SKIN SENSITIZATION - Category 1

**SARA 313** : This product (does/not) contain toxic chemicals subject to the reporting requirements of SARA Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR 372.

Product name	CAS number	%
Not applicable.		

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

# State regulations

Massachusetts : The following components are listed: Distillates (petroleum), hydrotreated heavy paraffinic

**New York** : None of the components are listed. **New Jersey** : None of the components are listed. Pennsylvania : None of the components are listed.

#### California Prop. 65



WARNING: This product can expose you to chemicals including Benzene and Lead and Lead Compounds, which are known to the State of California to cause cancer and birth defects or other reproductive harm. This product can expose you to chemicals including Sulphur Dioxide, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Ingredient name	No significant risk level	Maximum acceptable dosage level
Sulphur Dioxide	-	Yes.
Benzene	Yes.	Yes.
Lead and Lead Compounds	Yes.	Yes.

# Section 16. Other information

Revision date : 03/01/2023 : 05/28/2020 Supersedes

Revised Section(s) : KMK Regulatory Services Inc. Prepared by

Notice to reader
THE INFORMATION CONTAINED IN THIS SDS RELATES ONLY TO THE SPECIFIC MATERIAL IDENTIFIED. IT DOES NOT COVER USE OF THAT MATERIAL IN COMBINATION WITH ANY OTHER
MATERIAL OR IN ANY PARTICULAR PROCESS. IN COMPLIANCE WITH 29 C.F.R. 1910.1200(g), CHS HAS PREPARED THIS SDS IN SEGMENTS, WITH THE INTENT THAT THOSE SEGMENTS BE
READ TOGETHER AS A WHOLE WITHOUT TEXTUAL OMISSIONS OR ALTERATIONS. CHS BELIEVES THE INFORMATION CONTAINED HEREIN TO BE ACCURATE, BUT MAKES NO
REPRESENTATION, GUARANTEE, OR WARRANTY, EXPRESS OR IMPLIED, ABOUT THE ACCURACY, RELIABILITY, OR COMPLETENESS OF THE INFORMATION OR ABOUT THE FITNESS OF
CONTENTS HEREIN FOR EITHER GENERAL OR PARTICILIAR PLIRPOSES. PERSONS REVIEWING THIS SDS SHOULD MAKE THEIR OWN DETERMINATION AS TO THE MATERIAL'S CONTENTS HEREIN FOR EITHER GENERAL OR PARTICULAR PURPOSES. PERSONS REVIEWING THIS SDS SHOULD MAKE THEIR OWN DETERMINATION AS TO THE MATERIAL'S SUITABILITY AND COMPLETENESS FOR USE IN THEIR PARTICULAR APPLICATIONS.



OUR ENERGY COMES THROUGH!

