

Cenex Premium #2 ULSD Includes: Ruby Fieldmaster (B2&B5), Roadmaster (B2&B5)

Physical Property	<u>ASTM</u> Method	<u>Specifications</u> Min Max	
Gravity API	D4052	Report	
Flash, ^O F, PM	D93	126	
Kin. Viscosity, 104 ⁰ F, cSt	D445	1.7	4.1
Corrosion Test 3 hrs. at 122 ⁰ F	D130		#1
Sulfur, Wt. %	D5453 (2)		15 mg/kg
Pour Point, ^O F	D97		-15
Cloud Point, ^O F	D2500/D5733		+6 North
			+14 South
Ash, Wt. %	D482		0.01
Distillation, ^O F, 760 mm	D86		
90% Recovered		540	640
End Point		Report	
Water & Sediment, Vol. %	D2709		0.05
Cetane Number	D613/D6890	46.0	
Carbon Res. 10% Residuum	D524		0.35
Thermal Stability	D6468		
W unit		75	
% reflection or Y unit		82	
Haze (procedure 2)	D4176		2
Lubricity	D6079		430

Additional information:

Premium Additive Package is present Cloud point and pour point max October 1 through March 1 Cloud and pour point max may be higher due to region product is sold Meets or exceeds ASTM 975 specification The difference between Roadmaster XL and Ruby Fieldmaster is that the FM contains red dye

Document Name: Roadmaster_Fieldmaster Author: CE Revision: 2.5 Effective Date: 11/1/2022