

SAFETY DATA SHEET

SDS: PHY0274AB

Cenex® FG Hydraulic ISO 150

Issuing Date 07-19-2023 Revision Date 07-19-2023 **Revision Number** 2

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product Identifier

Product Name Cenex® FG Hydraulic ISO 150

Other means of identification

Product Code(s) PHY0274AB

Synonyms No information available

Recommended use of the chemical and restrictions on use

Identified uses Lubricant

Uses advised against Consumer use

Details of the supplier of the safety data sheet

Manufacturer

CHS Inc. P.O. Box 64089 Mail Station 525 St. Paul, MN 55164-0089 SDS Information 1-651-355-8445 **Emergency Telephone Number**

CHEMTREC: 1-800-424-9300 (NORTH AMERICA)

+1-703-527-3887 (INTERNATIONAL)

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Label Elements

Emergency Overview				
Signal Word	None			

Appearance Clear, amber colored

Response

None.

SDS:

PHY0274AB

Cenex® FG Hydraulic ISO 150

Issuing Date 07-19-2023 Revision Date 07-19-2023 Revision Number 2

Eyes None. Skin None. Inhalation

None. Ingestion None.

None. **Spill** None.

Fire

Storage None. Disposal None.

Hazards not otherwise classified (HNOC)

None

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No	Weight-%
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	90 - 100
White Mineral Oil	8042-47-5	1 - 5

The producer of "PHY0274AB" declares that it contains less than 3% DMSO extractable material by IP-346

4. FIRST AID MEASURES

First Aid Measures

Eye Contact Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

Skin Contact Wash off immediately with soap and plenty of water while removing all contaminated clothes

and shoes. Consult a physician if necessary.

Inhalation Consult a physician. If not breathing, give artificial respiration.

Ingestion Do NOT induce vomiting. Drink plenty of water.

Most important symptoms and effects, both acute and delayed

Symptoms None known.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Flash Point 221 °C - 430 °F

Cenex® FG Hydraulic ISO 150

Issuing Date 07-19-2023 Revision Date 07-19-2023 Revision Number 2

Suitable Extinguishing Media Water spray, Carbon dioxide (CO2), Foam, Dry chemical

<u>Unsuitable Extinguishing Media</u> Do not use a solid water stream as it may scatter and spread fire.

Specific Hazards Arising from the

Chemical

Thermal decomposition can lead to release of irritating gases and vapors.

Explosion Data

Sensitivity to Mechanical Impact Not impact sensitive.

Sensitivity to Static Discharge May be ignited by friction, heat, sparks or flames.

Protective Equipment and Precautions for Firefighters

Wear self-contained breathing apparatus and protective suit.

NFPA

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal PrecautionsDo not touch or walk through spilled material. Remove all sources of ignition.

Environmental Precautions

Environmental Precautions Do not allow material to contaminate ground water system. Local authorities should be

advised if significant spillages cannot be contained. Refer to protective measures listed in

Sections 7 and 8.

Methods and material for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so. Absorb spill with inert material (e.g. dry

sand or earth), then place in a chemical waste container.

Methods for Cleaning up

Use personal protective equipment. Take up mechanically, placing in appropriate containers

for disposal. Clean contaminated surface thoroughly.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. When using, do not

eat, drink or smoke. For personal protection see section 8.

Conditions for safe storage, including any incompatibilities

Technical measures/Storage

conditions

Keep containers tightly closed in a dry, cool and well-ventilated place.

Incompatible products Strong oxidizing agents. Strong acids. Strong bases.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Cenex® FG Hydraulic ISO 150

Issuing Date 07-19-2023 Revision Date 07-19-2023 Revision Number 2

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Petroleum distillates, hydrotreated	TWA: 5 mg/m ³	TWA: 5 mg/m ³	IDLH: 2500 mg/m ³
heavy paraffinic		(vacated) TWA: 5 mg/m ³	TWA: 5 mg/m ³
			STEL: 10 mg/m ³
White Mineral Oil	TWA: 5 mg/m ³	TWA: 5 mg/m ³	IDLH: 2500 mg/m ³
		(vacated) TWA: 5 mg/m ³	TWA: 5 mg/m ³
			STEL: 10 mg/m ³

Appropriate engineering controls

Engineering Measures Showers

Eyewash stations Ventilation systems.

Individual protection measures, such as personal protective equipment

appropriate when handling the bulk formulation.

Skin and Body Protection Long sleeved clothing. Protective gloves.

Respiratory Protection No protective equipment is needed under normal use conditions. If exposure limits are

exceeded or irritation is experienced, ventilation and evacuation may be required.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical state Liquid Appearance Clear, amber colored

Odor Hydrocarbon-like
Odor threshold No information available

<u>Property</u> <u>Values</u>

Melting Point / Freezing Point No data available **Boiling Point/Range** no data available 221 °C / 430 °F **Flash Point Upper flammability limit:** No data available **Lower Flammability Limit** No data available Vapor pressure No data available **Vapor Density** < 1 (Air = 1)**Specific Gravity** 0.876 Water solubility nealiaible

Partition Coefficient: n-octanol/water no data available
Autoignition Temperature No data available

Hyphen

Viscosity, kinematic 150 cSt @ 40°C

10. STABILITY AND REACTIVITY

reactivity No information available

Cenex® FG Hydraulic ISO 150

Issuing Date 07-19-2023 Revision Date 07-19-2023 Revision Number 2

<u>Chemical stability</u> Stable under recommended storage conditions

Possibility of Hazardous Reactions None under normal processing

<u>Conditions to Avoid</u> Heat, flames and sparks Contact with other chemicals

<u>Incompatible Materials</u> Strong oxidizing agents. Strong acids. Strong bases.

Hazardous Decomposition Products Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke)

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information Product does not present an acute toxicity hazard based on known or supplied information

Inhalation May cause irritation of respiratory tract.

Eye Contact Contact with eyes may cause irritation.

Skin Contact May cause irritation.

Ingestion There is no data available for this product.

	Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Petro	oleum distillates, hydrotreated	> 15 g/kg (Rat)	> 5000 mg/kg (Rabbit)	= 2062 ppm (Rat) 4 h
	heavy paraffinic	> 24 g/kg (Rat)		
	64742-54-7			
	White Mineral Oil	> 5000 mg/kg (Rat) > 24 g/kg (-	= 2062 ppm (Rat) 4 h
	8042-47-5	Rat)		

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

The producer of "PHY0274AB" declares that it contains less than 3% DMSO extractable material by IP-346

SensitizationNo information available.Mutagenic EffectsNo information available.CarcinogenicityNo information available.

Reproductive toxicityNo information available.

Target organ effects Respiratory system, Eyes, Skin.

Numerical measures of toxicity - Product Information

Cenex® FG Hydraulic ISO 150

Issuing Date 07-19-2023 Revision Date 07-19-2023 Revision Number 2

12. ECOLOGICAL INFORMATION

Ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Petroleum distillates,		LC50> 5000 mg/L		EC50 > 1000 mg/L 48 h
hydrotreated heavy paraffinic 64742-54-7		Oncorhynchus mykiss 96 h		_
White Mineral Oil		LC50> 10000 mg/L Lepomis		
8042-47-5		macrochirus 96 h		

Persistence and Degradability No information available.

Bioaccumulation No information available.

Mobility The product is insoluble and floats on water.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste Disposal Methods Dispose of in accordance with local regulations

Contaminated Packaging Do not re-use empty containers. Empty containers should be taken to an approved waste

handling site for recycling or disposal

14. TRANSPORT INFORMATION

DOT Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA Complies DSL/NDSL Complies NDSL Complies **EINECS** Not determined **ELINCS** Not determined **ENCS** Not determined Complies **IECSC KECL** Not determined **PICCS** Not determined AICS Complies

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

Cenex® FG Hydraulic ISO 150

Issuing Date 07-19-2023 Revision Date 07-19-2023 Revision Number 2

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

EPCRA: Emergency Planning and Community Right-to-Know Act

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

Clean Water Act

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material does not contain any components with a CERCLA RQ.

U.S. State Right-to-Know

<u>Regulations</u>

California Proposition 65

This product contains the following Proposition 65 chemicals:

Chemical name		California Prop. 65	
	Ethyl acrylate - 140-88-5	Carcinogen	

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Petroleum distillates, hydrotreated		X	X
heavy paraffinic			
64742-54-7			
White Mineral Oil		X	X
8042-47-5			
2-Ethylhexyl acrylate	X	X	X
103-11-7			
Ethyl acrylate	X	X	X
140-88-5			

NFPA

16. OTHER INFORMATION

Issuing Date07-19-2023Revision Date07-19-2023Reason for revisionInitial Release.

Disclaimer

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing,

SDS: PHY0274AB

Cenex® FG Hydraulic ISO 150

Issuing Date 07-19-2023 Revision Date 07-19-2023 Revision Number 2

storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The

storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet