

# Auto Gold<sup>®</sup> Multi-Vehicle ATF



## Synthetic Blend Automatic Transmission Fluid

### General Description

Auto Gold<sup>®</sup> Multi-Vehicle ATF synthetic blend automatic transmission fluid contains an advanced additive system along with specially selected mineral and synthetic base oils that provide service fill performance in a wide variety of automatic transmissions. It provides protection that meets or exceeds the industry's highest quality standards.

It includes specifications of most GM, Ford, Chrysler, Jeep, Saturn, Honda/Acura, Toyota, Nissan, Mitsubishi, Kia/Hyundai, Mercedes, BMW, VW/Audi and other transmissions. Always check the owner's manual for details.

Auto Gold Multi-Vehicle ATF is a balanced field tested formulation that gives assurance of the best possible wear protection on gears and transmission parts for a longer life. Excellent friction and anti-shudder durability for smooth and consistent shifting. Improved low temperature operability, resistance to high temperature oxidation and thermal degradation along with corrosion and foam inhibitors for year around protection. In addition, good compatibility with seal material minimizes leaks. It contains a shear-stable polymer that minimizes oil viscosity change over a wide temperature range. All these performance features provide enhanced transmission performance and life.

Not suitable for use in CVTS (continuously variable transmissions), DCTS (dual clutch transmissions) Mercon LV, Ford Type F, Allison TES-295 and TES 389

### Features and Benefits

- **Multi-Vehicle Capability:** Formulated to meet the stringent wear, friction, and operational requirements of most automatic transmissions for a smooth driving experience.
- **Wear Protection:** The highest level of wear protection for gears and internal moving parts allowing for maximum transmission life.
- **Friction Retention:** Uniquely balanced frictional properties provide anti-shudder durability, smooth shifting and precise lock-up throughout the service interval.
- **High Temperature Protection:** Excellent oxidation and thermal protection that reduces sludge, varnish, and deposits for longer life.
- **Cold Temperature Operability:** Good cold temperature flow characteristics provides ease of pumping, quick start up, smooth shifting, even at low temperatures.

### Typical Application

Suitable for use in applications where manufacturers recommend:

- Dexron VI\*,III,II, Type A, Suffix A
- Mercon V,SP\*,138CJ,166H
- Chrysler/Jeep +4,+3
- Most U. S., Asian and European Cars
- JASO 1A, ZF, Voith transmissions
- Allison C-4/C-3

\*Does not meet the lower viscosity requirement of these fluids. See Auto Gold Multi-Vehicle ATF sell sheet for more transmission recommendation details.

PDS-91-11

# Auto Gold<sup>®</sup> Multi-Vehicle ATF

## Synthetic Blend Automatic Transmission Fluid

### Typical Properties

Viscosity, cSt @ 40°C	32.9
@ 100°C	7.3
Viscosity Index	197
Brookfield @ -40 cP	13,000
API Gravity / Lbs gal	31.1 / 7.25
Pour Point, °F / °C	-58 / -51
Flash Point, °F / °C	385 / 196
Color	Red

### Typical Customer

Owners and operators of:

- Most GM, Chrysler, Ford, European, and Asian brands of automobiles and light trucks.
- Quick Lubes.
- Automobiles/Trucks/Buses calling for ATF fluids in automatic transmissions.
- Power Steering units calling for Mer/Dex ATF fluids.
- Hydraulic systems calling for ATF fluids.

The typical properties listed reflect the general characteristics of the product, and are not manufacturing specifications. Normal batch-to-batch variations should be expected.

### Auto Gold<sup>®</sup> Multi-Vehicle Synthetic Blend ATF recommended for these applications

ATF Type A, Suffix A	Hyundai NWS-9368*	Nissan 402, Matic-D, Matic-J, Matic-K, Matic-S*
Aisin Warner AW-1*	Hyundai/Kia SP-II, SP-III, SP-IV	Shell 3403, LA2634
Allison C-4	Idemitsu K17	Subaru ATF, ATF-HP
Audi G 052 025, G 052 162, G 052 990	JASO 1-A	Suzuki 3317
BMW 7045E, LA2634, LT 71141	JWS 3309, 3324*	Texaco ETL-7045E, ETL-8072B, N402
Chrysler +3, +4, MOPAR AS68RC	Kia Red-1	Toyota T-III, T-IV, WS*, (JWS3324*)
DEXRON <sup>®</sup> , II, IID, IIE, IIIF, IIIG, IIIH, VI*	MAN 339F, 339V1, 339Z1, 339Z2	Voith 55.6335.XX (G607), 55.6336.XX* (G1363*)
Esso LT 71141	Mazda ATF-M III, ATF-MV	Volvo Passenger Car, (4/6 speed), 97340, 97341
Ford MERCON <sup>®</sup> , MERCON <sup>®</sup> SP*, MERCON <sup>®</sup> V, FNR5	Mercedes Benz 236.1, 236.2, 236.3, 236.5, 236.6, 236.7, 236.9, 236.10, 236.11	VW G-052 025, G-052-162, G-055 025
Honda ATF-Z1, DW-1*	Mitsubishi Diamond SP-II, SP-III, SP-IV*, ATF J2*	ZF TE-ML 03D, 04D, 05L, 09, 11B, 14A, 16L, 17C

\*Recommended for use, although Auto Gold Multi-Vehicle ATF does not satisfy the lower viscosity requirements.

### Not recommended for these applications

Allison TES-295, TES-389	CVT (Continuous Variable Transmission)
Ford Type F, MERCON <sup>®</sup> LV	DCT (Dual Clutch Transmission)

### Health & Safety

A complete safety data sheet is available by calling 1-651-355-8438 or visit [www.cenex.com](http://www.cenex.com).