

Maxtron® Enviro-EDGE®



Full-Synthetic Diesel Engine Oil 5W-40, CK-4/SN

General Description

Maxtron® Enviro-EDGE® is an advanced full-synthetic 5W-40 diesel engine oil. This premium heavy duty diesel engine oil is engineered for optimal fuel economy, wide temperature range performance and superior protection of all Tier IV and newer model year low emission engines and exhaust after treatment systems. Maxtron Enviro-EDGE has a unique, backward-compatible formulation that provides additional protection for older engines.

Enhanced, industry-leading anti-oxidant performance and aeration protection give Maxtron Enviro-EDGE the highest level of field tested durability for longer engine life in fleet, construction, and agriculture equipment under severe service and extreme temperature conditions. This performance is supported by extensive engine and field testing.

Maxtron Enviro-EDGE is proven to protect Diesel Particle Filter (DPF) against ash build up and displays excellent TBN retention, protects against viscosity shear loss, and leads to a decrease in oil consumption. In addition, this oil provides improved engine protection from soot, deposits, varnish, wear and acid accumulation.

Expect excellent performance in these applications:

- Four-stroke naturally aspirated and turbocharged diesel engines.
- All Tier IV and newer low emission engines with exhaust after treatments devices.
- Pre-Tier IV engines specifying an older API or OEM oil performance category.
- When using ultra low sulfur diesel fuel.
- When the manufacturer recommends the use of 5W-40 diesel engine oils.

Features and Benefits

- **Oil Durability:** This full-synthetic oil includes advanced oxidation protection and enhanced shear stability to provide longer oil and engine life within the increased thermal demands of today's engines.
- **Fuel Economy:** Demonstrated in engine and road tests to provide up to 1.2% improved fuel economy, compared to 15W-40 oils.
- **Oil Pumpability:** Exceeds the pumpability requirements of 5W-40 oils, providing improved lubrication to critical engine parts which reduces wear during cold temperature start-ups.
- **Wear Control:** Provides improved wear control over previous performance classifications and exceeds the requirements of the newest industry tests.
- **Exceptional Soot and Deposit Control:** Maxtron Enviro-EDGE demonstrates outstanding soot control that exceeds the requirements of both new and older engines, which is critical for reducing engine wear and extending engine life.
- **TBN Retention:** A high Total Base Number (TBN) and excellent TBN retention means more combustion contaminants (deposits, soot, acids) can be neutralized during the course of a drain interval.
- **Volatility Control:** Less oil volatility provides reduced consumption, lower deposits, and a reduced amount of oil in the emission system.
- **Extended Drain:** Maxtron Enviro-EDGE is capable of extended drain service with new and older engines. This should be determined with a LubeScan® used oil analysis program.

Maxtron® Enviro-EDGE®

Full-Synthetic Diesel Engine Oil 5W-40, CK-4/SN

Typical Applications

Maxtron Enviro-EDGE is designed to exceed the newest API and OEM service categories:

Mack EOS-4.5, EO-O Premium Plus, EO-N **Volvo** VDS-4.5, VDS-4, VDS-3, **Cummins** CES 20086, CES 20081, **Caterpillar** ECF-3, EC-/2, **Detroit Diesel** DFS 93K222, DFS 93K218, **Daimler MB** 228.31, **Renault** RLD-4, RLD-3, **MAN** M-3575, **MTU** Category 2.1, **ACEA** E9-2012, E7, **Ford** WSS-M2C171-F1, **Chrysler** MS 10902

Typical Customers

Operators of heavy duty diesel engines:

- Fleets, Contractors, Agriculture
- On- and off-highway engines operating in extreme temperatures
- Diesel passenger cars and light trucks

Typical Properties

SAE Grade	5W-40
API Service	CK-4, CJ-4, CI-4 Plus, CI-4, /SN
API Gravity/Density lbs/gal	34.1/7.12
Viscosity @ 40°C, cSt	94.3
Viscosity @ 100°C, cSt	15.2
Viscosity Index	170
Pour Point, °F (°C)	-49 (-45)
MRV-TP1, cP	32800 @ -35°C
CCS Viscosity, cP	5930 @ -30°C
Total Base No. (TBN)	11.0
HTHS Viscosity, mPa-s ASTM D4683	4.0
Sulfated Ash Wt. %	1.1

The typical properties listed reflect the general characteristics of the product, and are not manufacturing specifications. Normal batch-to-batch variations should be expected.

Health & Safety

A complete safety data sheet is available by calling 1-651-355-8438 or visit cenex.com/sds-library.